







« REXI-HC

GAS REGULATORS FOR MEDIUM PRESSURE - HIGH CAPACITY

Operating pressure:	20 bar
Connection:	DN25, DN40, DN50 (Flanged)
Output pressure:	From 10 to 4500 mbar
Accuracy class AC:	Up to 5
Lock-up pressure class SG:	Up to 10
Available with:	OPSO / UPSO & Relief Valve
Max Flow Capacity:	4500 Nm ³ /h



REXI HORIZONTAL » HEAD

GAS REGULATORS FOR MEDIUM PRESSURE

Operating pressure:	20 bar
Connection:	1", 1 ½", 2", DN40, DN50
Output pressure:	From 10 to 4500 mbar
Accuracy class AC:	Up to 5
Lock-up pressure class SG:	Up to 10
Available with:	OPSO / UPSO & Relief Valve
Max Flow Capacity:	600 Nm ³ /h









REXI VERTICAL HEAD

GAS REGULATORS FOR MEDIUM PRESSURE

20 bar
1", 1 ½", 2", DN40, DN50
From 10 to 4500 mbar
Up to 5
Up to 10
OPSO / UPSO & Relief Valve
600 Nm ³ /h

MADE IN ITALY

RG



GAS REGULATORS
FOR LOW PRESSURE WITH SSV

Operating pressure:	500 mbar/5 Bar
Connection:	1/2" to DN100
Output pressure:	From 6 to 480 mbar
Class:	A
Available with:	OPSO / UPSO

MADE IN ITALY



GAS GOVERNORS »

Operating pressure: 500 mbar/1 Bar/2 Bar/5 Bar Body: Aluminium Connection: From 1/2" to DN100 With or without filter Available: Test Point available on request

MADE IN ITALY





SLAM SHUT VALVES



Operating pressure:	20 bar
Connection:	REXI BLOCK 1", 1 ½", 2", DN40, DN50
	REXI BLOCK - HC DN25, DN40, DN50
OPSO:	From 30 mbar to 6 bar
OPSO:	From 6 mbar to 3,5 bar
Accuracy class AC:	Up to 10



AUTOMATIC » SOLENOID VALVES

VALVES FAST OPENING OR SLOW OPENING

Operating pressure:	360 mbar/6 Bar
Connection:	From 1/2" to DN150
Class:	А
Body:	Aluminium
Type:	Fast Opening/Closing & Slow Opening/Fast Closing







« MANUAL SOLENOID VALVES

ATEX APPROVED VERSION AVAILABLE

Operating pressure:	550 mbar/6 Bar
Connection:	From 1/2" to DN200
Body:	Brass from 1/2" to 2" Aluminium from DN65 till DN200
Type:	Normally Closed/Normally Open

MADE IN ITALY



« RELIEF VALVES

Operating pressure:	1 Bar
Body:	Aluminium
Connection:	From 1/2" to 2"
Relief ranges:	20-120mbar/100-450mbar/ 200-600mbar

MADE IN ITALY

GAS FILTERS »



Operating pressure:	6 Bar/10 Bar
Connection:	From 1/2" to DN200
Body:	Aluminium
Filtration degree:	50 micron/10 micron
TEST DOINIT/SCDEW/ DI LIG I	DETERSON DI LIG available on request





« OIL FILTERS



Body:	Aluminium / Plastic
Filtration degree:	15/44/100/200/300 micron
Size:	From 1/4" to 1 1/2"
Available with: element	Drain valve / heating



ACCESSORIES *

GAS GAUGES & BALL VALVES



From 4 to 16bar / Operating pressure: From 40 to 600mbar

1/4", 3/8", 1/2" Connection: 63mm/80mm/100mm Body: 2.5/1.6

MADE IN ITALY



Operating pressure: **Depending on models** PN5/PN10/PN16

Body: Brass from 1/4" to 4" (Threaded) Cast iron from DN15 to DN250 (Flanged)

Connection: From 1/2" to 4"

*different handles types available







geca

GECA S.r.I.

Via E. Fermi, 98 | 25064 Gussago (BS) | ITALY Tel. +39 030 3730218

Fax +39 030 3730228 E-mail: info@gecasrl.it gecasrl.it



Tecnocontrol S.r.l.

Via Miglioli, 47 | 20054 Segrate (MI) | ITALY

Tel. $+39\ 02\ 26922890$ Fax $+39\ 02\ 2133734$

E-mail: info@tecnocontrol.it tecnocontrol.it



CPF Industriale S.r.l.

Via E. Fermi, 98 | 25064 Gussago (BS) | ITALY Tel. +39 030 310461

lel. $+39\ 030\ 310461$ Fax $+39\ 030\ 310465$

E-mail: info@cpfindustriale.it cpfindustriale.it

Marchi:



